

WAKRA

Maschinen & Diamantwerkzeuge

DICOREL 2010S



Dicorel 2010-S

Rißsaniierung


Mit der extrem wendigen und starken Trockenschnittfräse **DICOREL 2010S** werden wilde Risse im Asphalt mit einem Diamantwerkzeug bis auf den gesunden Untergrund ausgefräst. Das anfallende Fräßgut und der Staub werden automatisch durch die integrierte Absaugung über einen zwei Zyklonabscheider in einen Behälter aufgenommen. Die so entstandene wilde Arbeitsfuge ist weitgehend sauber und kann ohne Verzögerung mit heißer Vergußmaße ausgegossen und abgedichtet werden. Dank dem Arbeitsvorschub und der starken Motorenleistung sind hohe Tagesleistungen möglich.

- Elektromotor
- Der Fahrtrieb ist durch ein hydrostatisches Getriebe bis zu 4m/min regelbar
- Der Blattaushub arbeitet elektro hydraulisch
- Umweltfreundlich

Road Maintenance

With the extremely agile dry cutting milling machine **DICOREL 2010S** wild cracks in asphalt or concrete will be milled out with a dry cutting diamond tool up to the healthy ground. Thanks to the integrated vacuum calendar, which soaks up the arising milling dust automatically into a container, the so treated new joint can be refilled and sealed immediately with a hot filling and sealing casting compound. The **DICOREL 2010-S** with it pushing forward unit and it powerful petrol engine, gives high day outputs and the worker doesn't get tired at this.

- Electric motor,
- No water is required
- Reduced emissions to the environment
- The traction drive is by a hydraulic transmission up to 4m/min adjustable
- The saw blade is raised electro-hydraulic



Technische Daten / Technical Data

DICOREL	2010-S
Motor / petrol engine	2-Zyl. Benzinmotor mit E-Start / petrol engine with E-start 16.9kW, 23PS, @3600 upm
Vorschub / feed	Regelbar bis ca. / adjustable up to 4m/min
Blattdurchmesser / diameter of the blade	Ø 150mm
Schnitttiefe / cutting depth	30mm
Blattaushub / excavation of the sheet	Elektro hydraulisch Electro-hydraulic
Gewicht / weight	ca. 225kg